

Mobile Axial Hydraulic Pumps

Variable Displacement Load Sense Control

Certified Power
SOLUTIONS®



The Eaton® X20 portfolio of open-circuit piston pumps is built to maximize machine performance and productivity. With sophisticated controls that enhance system efficiency and a compact design that delivers incredible power, the X20 portfolio empowers mobile machine operators to do more work in less time using less fuel.

Excellent Pressure Responsiveness

The X20 portfolio delivers the fastest response and recovery times in the open-circuit piston segment, helping customers get the job done faster.

Simplified Pump Architecture

The X20 pump has 25% fewer components than traditional pumps, reducing the number of leak points and simplifying maintenance.

Compact Package Size

The X20 portfolio's small size satisfies Tier 4 requirements and provides more flexibility when designing the engine compartment.

One-Piece Housing

Single-piece pump housing removes leak points and makes maintenance faster and easier versus more complicated multi-piece housings.



420 Series
80 cm³/rev



620 Series
98 cm³/rev

Eaton's 420 Series is available with displacements of 41cc, 49cc, 62cc, and 80cc for operating speeds at 2,650 rpm. A strong, field-proven rotating group allows the pumps to handle pressures to 280 bar (4060 psi) continuous and 320 bar (4600 psi) intermittent.

Eaton's 620 Series is currently available in 98cc (5.98 in³/r) displacement. It is rated at 310 bar and is capable of generating over 100 kW (134 hp). The 620 design also incorporates new advances in product reliability.



DOWNLOAD
THIS SHEET

Series 420		Units	ADU041 ADU049		ADU062	ADU080
	Displacement	cc/r (in ³ /r)	41.0 (2.50)	49.2 (3.00)	62.3 (3.80)	80.0 (4.88)
	Mounting	2 Bolt B, 2 Bolt C, 2/4 Bolt C				
	Pressure	Continuous	bar (psi)	280 (4060)	280 (4060)	210 (3050)
		Intermittent ²		320 (4600)	320 (4600)	230 (3335)
		Peak ³		350 (5000)	350 (5000)	250 (3625)
	Speed ⁴	At 1 bar abs (0 psig)	rpm	2650	2650	2600
		At.85 bar abs (5 in.Hg)		2450	2450	2400
		At 2 bar abs (15 psig)		2950	2950	2800
		Max (standby)		3600	3600	3600
		Min		600	600	600
Power	Max (theoretical)	kW (hp)	50.7 (68.0)	60.8 (81.5)	75.6 (101.3)	61.7 (82.7)
	Standby		.98 (1.3)	.98 (1.3)	1.1 (1.5)	1.4 (1.9)
Torque	Max (theoretical)	Nm (lb-ft)	183 (135)	219 (162)	278 (205)	268 (198)
Weight	Single Seal ¹	kg (lbm)	22.9 (50.4)	22.9 (50.4)	23.8 (52.4)	24.2 (53.4)
	Dual Seal ¹		24.1 (53.1)	24.1 (53.1)	25.0 (55.1)	25.4 (56.1)
Bearing life ⁵	At 140 bar (2030 psi)	B10 Hours	103,650	55,580	33,500	17,150
	At 210 bar (3045 psi)		26,830	14,380	8,670	4,440
	At 280 bar (4060 psi)		10,280	5,510	3,320	N/A
Mass moment of inertia		Nm-sec ²	0.003	0.003	0.005	0.006
		(lb-in-sec ²)	-0.029	-0.029	-0.040	-0.052

Series 620		Units	ADY074 ADY098	
	Displacement	cc/r (in ³ /r)	74.4 (4.54)	98.0 (5.98)
	Mounting (SAE)	4 Bolt C, 2/4 Bolt C		
	Pressure	Continuous	bar (psi)	310 (4495)
		Intermittent ³		280 (4060)
		Peak ⁴		346 (5020)
	Speed ⁵	Rated	rpm	320 (4600)
		Max		373 (5410)
		Min		2400
				2200
Power	Max (theoretical)	kW (hp)	2880	2640
	Standby		600	600
Torque	Max (theoretical)	Nm (lb-ft)	92.3 (123.7)	100.6 (134.9)
Weight ¹		kg (lbf)	2.1 (2.8)	2.6 (3.5)
			367.3 (270.9)	436.7 (322.1)
Bearing life ⁶	At 140 bar (2030 psi)	B10 Hours	43.5 (96.1)	45.9 (101.3)
	At 210 bar (3045 psi)		125,200	81,400
	At 280 bar (4060 psi)		32,900	21,400
	At 310 bar (4495 psi)		12,100	7,900
Mass moment of inertia		kg-m ²	8,600	
		(lbm-ft ²)	0.009	0.012
			-0.211	-0.279

FleetPilot^{IV}
BY CERTIFIED POWER



YOUR FLEET, YOUR WAY. FleetPilot by Certified Power combines equipment controls, hydraulics, and telematics in one adaptable platform. Built for precision and growth, it easily scales from one vehicle to a full fleet and supports everything from routine work to critical operations.

Explore your options at fleetpilot.com.

10.08.2025 / Certified Power Solutions



DOWNLOAD
THIS SHEET

Perrysburg, OH
(419) 873-7411

Fridley, MN
(952) 894-5700

Mundelein, IL
(847) 573-3800

Bridgeton, MO
(314) 344-3300

Des Moines, IA
(515) 244-7411

Dickinson, ND
(701) 225-8685